
SL-1

NT7D16 Data Access Card

Description and operation

Publication number: 553-3001-191

Document release: 3.0

Document status: Standard

Date: December 31, 1992

© 1990 Northern Telecom
All rights reserved.

Revision history

December 20, 1990

This is a new document issued for the NT7D16 Data Access Card.

December 1, 1991

Standard, release 2.0

December 31, 1992

Standard, release 3.0 reissued for technical updates. Changes are noted with revision bars in the margins.

Contents

About this document	1
References	1
Description	3
Features	3
Controls and indicators	4
Card status	4
Electronic Industries Association signal monitors	4
CONNECT	5
Port mode	5
Port number	5
Port select button	5
Wire test	5
Operation	7
Dialing operations	7
Port firmware in idle state	7
Call Set-up abort	7
Make Port Busy on loss of DTR	8
Inactivity timeout	8
Wire test mode	9
Independent storage of dialing parameters	10
User input	10
Operating modes	11
Selecting the proper mode for Modem connectivity	16
Mode 0	19

Configuring modems for mode 0	19
Programing DAC for mode 0 in service change LD11	20
Mode 1	22
Configuring modems for mode 1	22
Programing DAC for mode 1 in service change LD11	23
Mode 2	23
Configuring Hayes 1200 for mode 2	23
Programing DAC for mode 2 in service change LD11	23
Mode 3	24
Configuring Hayes 1200 for mode 3	24
Programing DAC for mode 3 in service change LD11	24
Selecting the proper mode for Gateway connectivity	24
Mode 4	27
Programing DAC for mode 4 in service change LD11	27
Mode 5	28
Programing DAC for mode 5 in service change LD11	29
Mode 6	29
Programing DAC for mode 6 in service change LD11	29
Mode 7	29
Programing DAC for mode 7 in service change LD11	30
Selecting the proper mode for Host connectivity	30
Mode 8	32
Mode 9	33
Programing DAC for mode 9 in service change LD11	33
Mode 10	33
Programing DAC for mode 10 in service change LD11	34
Mode 11	34
Programing DAC for mode 11 in service change LD11	34
Selecting the proper mode for Terminal connectivity	35
Mode 12	36
Programing DAC for mode 12 in service change LD11	36
Mode 13	36
Programing DAC for mode 13 in service change LD11	36
Mode 14	37
Programing DAC for mode 14 in service change LD11	37
Mode 15	37
Programing DAC for mode 15 in service change LD11	38

Mode selection baud rates	38
Keyboard dialing	49
Initiating conditions	49
Echo	50
Prompts	50
Call abort	50
Autobaud	51
Auto parity	51
Dialing operation	51
Primary commands	52
Call (C)	52
Autodial (A)	53
Speed Call (S)	53
Ring Again	57
Not in service	60
No response from the system	60
Hayes dialing	61
Initiating conditions	62
Input requirements	62
Echo	62
Result codes and messages	63
Baud rate detection	64
Parity detection	65
Dialing operation	65
S registers	67
Reset Hayes parameters	69
Outbound calls	71
Inbound calls	72
Off Line mode	73

Specifications	75
QPC430 and QPC723 interfaces	75
Download parameters	75
System parameters	75
Operating parameters	76
Upload parameters	80
System database requirements	80
Power supply	82
EIA signals supported	82
Environmental	83
Reliability	83
 Installation	 85
Installing the Data Access Card in system option 11	85
Installing the Data Access Card in system options 21, 51, 61, 71, and 81	86
System compatibility	87
Port configuration	87
Cabling	89
Backplane pinout and signaling	94
Configuring the Data Access Card	97
DAC administration (LD11)	97
Printing the card parameters (LD20)	101
Connecting Apple Macintosh to the DAC	103
Upgrading systems	104
System options 21 and 21A upgrade	104
System options 51, 61, 71, and 81 upgrade	106
Segment 0	106
Segment 1	106
Segment 2	107
Segment 3	107

List of Figures

Figure 1	
NT7D16 Data Access Card faceplate	6
Figure 2	
DAC to modem connectivity	18
Figure 3	
DAC to Modem Pool connectivity	21
Figure 4	
DAC to Gateway connectivity	26
Figure 5	
DAC to Gateway—Inbound/Outbound connectivity	28
Figure 6	
DAC to Host connectivity	31
Figure 7	
DAC to Terminal connectivity	35
Figure 8	
Operating mode selection—RS422	78
Figure 9	
Operating mode selection—RS-232-C	79
Figure 10	
NT7D16 Data Access Card port connectors	88
Figure 11	
Cabling to the data equipment	90
Figure 12	
RJ-11 or RJ-45 jacks	91

Figure 13	
Patch panel layout	92
Figure 14	
Octopus cabling	93
Figure 15	
Macintosh to DAC connection—9-pin subminiature D	103
Figure 16	
Macintosh to DAC connection—mini-8 DIN	103

List of Tables

Table 1	
Wire test signal leads cycle counts	9
Table 2	
DAC mode of operation selection	14
Table 3	
Connect and disconnect protocol	39
Table 4	
Hayes dialing result codes and messages	64
Table 5	
AT dialing commands	66
Table 6	
Allowable S registers	68
Table 7	
Hayes parameters and S register reset values	70
Table 8	
Allowed outbound call command characters	72
Table 9	
Virtual key assignments	81
Table 10	
EIA signals supported (RS-232-C)	82
Table 11	
System option compatibility with the DAC	87
Table 12	
RS-232-C maximum line capacitance 2,500 μ F	89

Table 13	
RS-422 maximum line capacitance 60,000 μ F	89
Table 14	
RS-232-C and RS-422 pinouts for first three DAC ports	94
Table 15	
RS-232-C and RS-422 pinouts for last three DAC ports	96
Table 16	
???—was not numbered or titled in Word file	98
Table 17	
???—was not numbered or titled in Word file	101
Table 18	
???—was not numbered or titled in Word file	102